

AQUASWITCH II™ SENSORS

PRICE LIST

RESISTIVITY & CONDUCTIVITY/TDS

JANUARY 1, 2002

STANDARD MODELS — 316 Stainless Steel, with 10 Foot (3 Meter) Shielded Cable

PRICE

CS10	Resistivity 100PSI@100°C	\$200.00
CS10LS	Above CS10 in 6" length	\$256.00
CS51LC	Conductivity/TDS 100PSI@100°C (for 0-1 thru 0-5 µS/ppm Ranges)	\$155.00
CS51	Conductivity/TDS 100PSI@100°C (for 0-10 thru 0-100 µS/ppm Ranges)	\$155.00
CS51LS	Above CS51 in 6" length	\$211.00

STANDARD OPTIONS

Add dash number, and price to above sensor module selected

-T	Titanium - in place of stainless steel (CS51 & CS10)	\$33.00
-25	25' Shielded Cable	\$20.00
-100	100' Shielded Cable	\$70.00
-PV*	1/2" PVDF Fitting (replaces polypropylene)	\$35.00
-HPSS*	1/2" 316 Stainless Steel Fitting 200PSI@120°C (replaces polypropylene)	\$85.00

* Ordered separately add 'O', i.e. PVO or HPSSO.

Order Example:

For a standard resistivity sensor, "CS10" with temperature order: CS10-TP

TOTAL PRICE

\$254.00

SPECIAL ORDER MODELS — 316 Stainless Steel

CS40	Valve insertable 100PSI@150°C (1.0, 0.1 & 0.05)	\$325.00
CS50	Conductivity/TDS 100PSI@95°C (1.0 & 0.1)	\$145.00
CSA	Low cost Conductivity/TDS - NO Temperature Compensation 75PSI@60°C (0-10 thru 0-100 µS/ppm) (1.0)	\$42.00
CSATC	Low cost Conductivity/TDS 75PSI@60°C (0-10 thru 0-100 µS/ppm) (1.0)	\$72.00
	Above CSA Models for low pressure / low temperature applications -75PSI@60°C.	

SPECIAL ORDER OPTIONS NOTE: these options require longer lead times

Add dash number, and price to above sensor module selected.

-T	Above Special Order sensors in Titanium except CSA modules	POR
-TP	Temperature sensor 0-200°C - NOT for CSA or CSATC	\$54.00
-WTV	Wet-Tap Valve for CS40 stainless steel (0.1 & 1.0 only)	\$300.00
-JB	Junction Box - Class I, Group D, Div. S, Explosion Proof, Weather Proof, Aluminum. For CS40.	\$120.00
-STF	SANITEC fitting for CS10, CS51 & CS51LC. State size, i.e. CS10-T-25-STF3/4. 1/2", 3/4", 1", 1 1/2", & 2"	\$110.00
	2 1/2", 3", & 4"	\$128.00
-25	25' Shielded Cable (standard sensor - 5 wire)	\$20.00
-100	100' Shielded Cable (standard sensor - 5 wire)	\$70.00
-25T	25' Shielded Cable (8 wire temperature sensor)	\$38.00
-100T	100' Shielded Cable (8 wire temperature sensor)	\$228.00

EXAMPLE:

For a CS40 Conductivity sensor w/a cell constant of 1.0, Wet-Tap Valve, and Temperature order: CS40-01-WTV-TP

TOTAL PRICE

\$679.00

ALL SPECIAL ORDER ITEMS ARE NON-RETURNABLE AND NON-REFUNDABLE.

Custom and OEM Monitors/controllers available, contact us with your special needs. Price and delivery upon request.

NOTE: Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.

Because of our policy of continuous product improvement, the Myron L Company reserves the right to make changes in design, specifications, and prices without notice.

Terms: 1% 10 days, net 30 days upon receipt of sufficient credit information.

Export orders: payment in advance, sight draft collection, or credit card (Visa/MasterCard/Amex).

6115 Corte del Cedro
Carlsbad, CA 92009-1516 USA
Tel: 760-438-2021
Fax: 800-869-7668 / 760-931-9189
www.myronl.com

Printed in U.S.A.

Built On Trust. Founded in 1957, the Myron L Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

MYRON L COMPANY

pH/Conductivity Instrumentation
Accuracy • Reliability • Simplicity

© Myron L Company 2002

ASSPL 07-02