

750 Series II

PRICE LIST

CONDUCTIVITY/TDS

MARCH 1, 2001

MONITOR/CONTROLLERS

<u>MODEL</u>		<u>PRICE</u>
756II	ANALOG MONITOR ONLY	\$350.00
757II	ANALOG MONITOR / CONTROLLER	\$410.00
758II	DIGITAL MONITOR / CONTROLLER	\$435.00
759II	DIGITAL MONITOR ONLY	\$375.00

RANGE

(Must select one, see page 2)

NO ADDITIONAL CHARGE

OPTIONS

-SC	SECOND ALARM/CONTROL MODULE	\$105.00
-4A	4-20mA SELF-POWERED ISOLATED OUTPUT MODULE (DIGITAL ONLY)	\$120.00
-3S	3 SENSOR INPUT MODULE W/ 3 FT/1 METER CABLE (CUSTOMER MOUNTED)*	\$93.00
-3R	3 RANGE SWITCH W/ 3 FT/1 METER CABLE (CUSTOMER MOUNTED)*	\$93.00
-3SR	ABOVE 3S AND 3R COMBINED (CUSTOMER MOUNTED)*	\$115.00
-PA	70db PIEZO ELECTRIC ALARM (MOUNTED ON FRONT PANEL)	\$35.00
-45	4 1/2 DIGIT BACKLIT LIQUID CRYSTAL DISPLAY (LCD)	\$70.00
-TP	TEMPERATURE MODULE 0-200°C, REQUIRES -TP SENSOR (DIGITAL ONLY)	\$140.00
-TH	TP/TPO ALARM/CONTROLLER HARNESS (REQUIRES SC & TP ABOVE)	\$53.00
-PC	POWERCORD 115VAC (8 FT. WITH PLUG AND STRAIN RELIEF)	\$22.00

SPECIAL ORDER OPTIONS

-24V	24 VAC ISOLATED POWER	\$18.00
-PTS	PANEL MOUNTED FULL SCALE TEST SWITCH	\$42.00
-TPA	TEMPERATURE MODULE 0-200°C, ABOVE -TP WITH ADJUSTABLE HYSTERESIS	\$142.00

EXAMPLE FOR A DIGITAL 0-2000 μ S CONDUCTIVITY CONTROLLER WITH 420 AND 4 1/2 DIGIT BACKLIT DISPLAY:

<u>MODEL</u>	<u>RANGE</u>	<u>OPTIONS</u>	<u>TOTAL PRICE</u>
758II	-121	-4A-45	\$625.00

ACCESSORIES

<u>MODEL</u>	<u>DESCRIPTION</u>	<u>PRICE</u>
SCO	SECOND ALARM/CONTROL MODULE ONLY	\$105.00
4AO	4-20mA SELF-POWERED ISOLATED OUTPUT MODULE (DIGITAL ONLY)	\$120.00
3SE	3 SENSOR INPUT MODULE WITH ENCLOSURE	\$175.00
3SO	3 SENSOR INPUT MODULE W/ 3 FT/1 METER CABLE (CUSTOMER INSTALLED)*	\$93.00
3REC	3 RANGE SWITCH WITH ENCLOSURE	\$175.00
3ROC	3 RANGE SWITCH WITH 3 FT/1 METER CABLE (CUSTOMER INSTALLED)*	\$93.00
3SROC	ABOVE 3S AND 3R COMBINED (CUSTOMER INSTALLED)*	\$126.00
3SREC	ABOVE 3S AND 3R COMBINED WITH ENCLOSURE	\$197.00
PAO	PIEZO ELECTRIC ALARM ONLY	\$35.00
45O	4 1/2 DIGIT BACKLIT LIQUID CRYSTAL DISPLAY (LCD)	\$130.00
TPO	TEMPERATURE MODULE 0-200°C (DIGITAL ONLY)	\$140.00
THO	TP/TPO ALARM/CONTROLLER HARNESS ONLY (REQUIRES SCO & TPO ABOVE)	\$53.00
TPC	CALIBRATION MODULE (TEMPERATURE MODULE)	\$119.00
PCO	POWERCORD 115VAC (8 FT. WITH PLUG AND STRAIN RELIEF) - NOT FOR 230VAC USE	\$18.00
SMP50	SURFACE MOUNTING PLATE	\$20.00
RA™	REMOTE ALARM	\$165.00
CC	NIST CERTIFICATE (WITHOUT SENSOR)	\$35.00
CCS	NIST CERTIFICATE (WITH SENSOR USING STANDARD SOLUTION)	\$80.00

* DOES NOT FIT INTO MONITOR/CONTROLLER ENCLOSURE, MUST BE MOUNTED SEPARATELY.
FOR SENSOR SELECTION SEE PAGE 3

ALL SPECIAL ORDER ITEMS ARE NON-RETURNABLE AND NON-REFUNDABLE.

Custom and OEM Monitors/Controllers available, contact us with your special needs.

Price and delivery upon request.

Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.

Because of our policy of continuous product improvement, the Myron L Company reserves the right to make changes in design, specifications, and prices without notice.

Terms: 1% 10 days, net 30 days upon receipt of sufficient credit information.

Export orders: payment in advance, sight draft collection, or credit card.

MYRON L COMPANY

pH/Conductivity Instrumentation
Accuracy • Reliability • Simplicity

CONDUCTIVITY/TDS RANGES

CONDUCTIVITY REQUIRES CS51 SENSOR (1.0 CONSTANT) EXCEPT AS NOTED

Add Range NUMBER below to instrument model number, i.e. 758II-"112" = 0-50 ppm Digital Monitor/controller.

756II, 757II, 758II & 759II

ANALOG & DIGITAL
CONDUCTIVITY/TDS
MONITOR/CONTROLLER

RANGE

Conductivity

0-1 μ S*	-101
0-1 ppm*	-102
0-2 μ S*	-103
0-2 ppm*	-104
0-5 μ S*	-105
0-5 ppm*	-106
0-10 μ S	-107
0-10 ppm	-108
0-20 μ S	-109
0-20 ppm	-110
0-50 μ S	-111
0-50 ppm	-112
0-100 μ S	-113
0-100 ppm	-114
0-200 μ S	-115
0-200 ppm	-116
0-500 μ S	-117
0-500 ppm	-118
0-1000 μ S	-119
0-1000 ppm	-120
0-2000 μ S	-121
0-2000 ppm	-122
0-5000 μ S/0-5 mS	-123
0-5000 ppm/0-5 ppt	-124
0-10,000 μ S/0-10 mS	-125
0-10,000 ppm/0-10 ppt	-126
0-20,000 μ S/0-20 mS	-127
0-20,000 ppm/0-20 ppt	-128
0-50,000 μ S/0-50 mS**	-129
0-50,000 ppm/0-50 ppt**	-130
0-100 mS**	-131
0-100 ppt**	-132
0-200 mS**	-133
0-200 ppt**	-134

*CS51LC CONDUCTIVITY SENSOR (0.1 CONSTANT) REQUIRED FOR THESE RANGES.

**CS52 SERIES CONDUCTIVITY SENSOR (10.0 CONSTANT) REQUIRED FOR THESE RANGES.

NOTE: Unless ppm/NaCl is specified with order, ppm type conductivity instruments will be configured for the Myron L "442™" Natural Water standard. For NaCl ppm/ppt add the letter "N" after the number.

High Pressure / High Temperature 250PSIG @ 205°C Models CS40HT (10, 1.0, 0.1 & 0.05) & CS41HT (1.0, 0.1 & 0.05) sensors available - Price & delivery on request.

Special Low Cost, low temperature/low pressure sensors - CSA & CSATC (1.0 constant) - available for some applications.

6115 Corte del Cedro
Carlsbad, CA 92009-1516 USA

Tel: 760-438-2021

Fax: 800-869-7668 / 760-931-9189

www.myronl.com

Built On Trust. Founded in 1957, the Myron L Company has become one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

**MYRON L
COMPANY**

pH/Conductivity Instrumentation
Accuracy • Reliability • Simplicity