

# SENSORS CONDUCTIVITY/TDS

# PRICE LIST

## 750 Series II MONITOR / CONTROLLERS

MARCH 1, 2001

### SENSORS WITH 10 Foot (3 Meter) SHIELDED CABLE

#### STANDARD MODELS — 316 STAINLESS STEEL

		<u>PRICE</u>
CS51LC	Conductivity 100PSI@100°C (for 0-1 thru 0-5 µS/ppm ranges)	\$155.00
CS51	Conductivity 100PSI@100°C (for 0-10 thru 0-20,000 µS/ppm ranges)	\$155.00
CS51LS	Above CS51 in 6" length	\$211.00
CS52	Conductivity 75PSI@95°C (for ranges above 20,000 µS/ppm)	\$180.00

#### STANDARD OPTIONS

Add dash number, and price to above sensor model selected

-T	Titanium - in place of stainless steel (CS51)	\$33.00
-25	25' shielded cable	\$20.00
-100	100' shielded cable	\$70.00
-PV*	1/2" PVDF fitting for CS51 only (replaces polypropylene)	\$35.00
-HPSS*	1/2" 316 stainless steel fitting for CS51 only 200PSI@120°C (replaces polypropylene)	\$85.00

\* Ordered separately add 'O', i.e. PVO or HPSSO.

#### SPECIAL ORDER MODELS — 316 STAINLESS STEEL

CS40	Conductivity/TDS valve insertable 100PSI@150°C (10.0, 1.0 & 0.1)	\$325.00
CS40HT	Above high temperature model 250PSI@205°C	\$430.00
CS41HT	Conductivity/TDS 250PSI@205°C (1.0, 0.1 & 0.05) W/JB	\$320.00
CS50	Conductivity/TDS 100PSI@95°C (1.0 & 0.1)	\$145.00
CSA*	Low cost Conductivity/TDS - no temp. comp. 75PSI@60°C (0-10 thru 0-20,000 µS/ppm) (1.0)	\$42.00
CSATC*	Low cost Conductivity/TDS 75PSI@60°C (0-10 thru 0-20,000 µS/ppm) (1.0)	\$72.00

\*Above CSA models for low pressure / low temperature applications - 75PSI@60°C.

#### SPECIAL ORDER OPTIONS

Add dash number, and price to above sensor model selected

-T	Above special order sensors in titanium except CSA models	POR
-TP	Temperature sensor 0-200°C - NOT for CSA or CSATC (Custom Order)	\$54.00
-WTV	Wet-tap valve for CS40 stainless steel (0.1 & 1.0 only)	\$300.00
-JB	Junction box - Class I, Group D, Div. S, explosion proof, weather proof, aluminum for CS40.	\$120.00
-STF	Stainless Steel Sanitec fitting for CS51 & CS51LC. State size, i.e. CS51-T-25-STF3/4. 1/2", 3/4", 1", 1 1/2", & 2" 2 1/2", 3", & 4"	\$110.00 \$128.00
-25	25' shielded cable (5 wire sensor standard)	\$20.00
-100	100' shielded cable (5 wire sensor standard)	\$70.00
-25T	25' shielded cable (8 wire temperature sensor)	\$38.00
-100T	100' shielded cable (8 wire temperature sensor)	\$228.00

#### EXAMPLE:

For a High Temperature conductivity sensor, "CS40" w/ a cell constant of 0.1, Wet-Tap Valve, and Temperature order:

CS40HT-01-WTV-TP **TOTAL PRICE** \$774.00

#### **ALL SPECIAL ORDER ITEMS ARE NON-RETURNABLE AND NON-REFUNDABLE.**

Custom and OEM Monitors/Controllers available, contact us with your special needs. Price and delivery upon request.

NOTE: Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.

Because of our policy of continuous product improvement, the Myron L Company reserves the right to make changes in design, specifications, and prices without notice.

Terms: 1% 10 days, net 30 days upon receipt of sufficient credit information.

Export orders: payment in advance, sight draft collection, or credit card.

6115 Corte del Cedro  
Carlsbad, CA 92009-1516 USA  
Tel: 760-438-2021  
Fax: 800-869-7668 / 760-931-9189  
www.myronl.com

Printed in U.S.A.

**Built On Trust.** Founded in 1957, the Myron L Company has become one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

**MYRON L  
COMPANY**  
pH/Conductivity Instrumentation  
Accuracy • Reliability • Simplicity

© Myron L Company 2001 750IICSPL 6-01