

750 Series II

PRICE LIST

RESISTIVITY

JUNE 1, 2001

MONITOR/CONTROLLERS

MODEL

PRICE

RESISTIVITY

751II	Resistivity Analog Monitor only	\$361.00
752II	Resistivity Analog Monitor/controller	\$421.00
753II	Resistivity Digital Monitor/controller	\$446.00
754II	Resistivity Digital Monitor only	\$386.00

RANGE

(Must select one, see page 2)

No additional charge

OPTIONS

-SC	Second Alarm/Control Module	\$105.00
-4A	4-20mA Self-Powered isolated output module (Digital only)	\$120.00
-3S	3 Sensor Input Module with 3 FT/1 meter cable (customer mounted)*	\$93.00
-3R	3 Range Switch with 3 FT/1 meter cable (customer mounted)*	\$93.00
-3SR	Above 3S and 3R combined (customer mounted)*	\$115.00
-PA	70db Piezo Electric Alarm (mounted on front panel)	\$35.00
-45	4 1/2 Digit backlit Liquid Crystal Display (LCD)	\$70.00
-TP	Temperature Module 0-200°C, requires -TP sensor (Digital only)	\$140.00
-TH	TP/TPO Alarm/Control Harness (requires SC & TP above)	\$53.00
-PC	Power Cord 115VAC (8 FT. with plug and strain relief)	\$22.00

SPECIAL ORDER OPTIONS

-24V	24 VAC Isolated Power	\$18.00
-PTS	Panel mounted full scale test switch	\$42.00
-SFP	Panel mounted set point adjustment	\$56.00
-TPA	Temperature Module 0-200°C, above -TP with adjustable hysteresis	\$142.00

EXAMPLE: A digital 0-20mA Resistivity Monitor/controller with 420 and 4 1/2 digit backlit display:

MODEL	RANGE	OPTIONS	TOTAL PRICE
753II	-11	-4A-45	\$605.00

ACCESSORIES

MODEL

DESCRIPTION

PRICE

SCO	Second Alarm/Control Module only	\$105.00
4AO	4-20mA Self-Powered isolated output module (Digital only)	\$120.00
3SE	3 Sensor Input Module with enclosure*	\$175.00
3SO	3 Sensor Input Module with 3 FT/1 meter cable (customer installed)*	\$93.00
3RE	3 Range Switch with Enclosure	\$175.00
3RO	3 Range Switch with 3 FT/1 meter cable	\$93.00
3SRO	Above 3S and 3R combined	\$126.00
3SRE	Above 3S and 3R combined with Enclosure	\$197.00
PAO	Piezo Electric Alarm only	\$35.00
45O	4 1/2 digit backlit Liquid Crystal Display (LCD)	\$130.00
TPO	Temperature Module 0-200°C, requires -TP sensor (Digital only)	\$140.00
THO	TP/TPO Alarm/Control Harness only (requires SCO & TPO above)	\$53.00
TPC	Calibration Module (temperature module)	\$119.00
PCO	Power Cord 115VAC (8 FT. with plug and strain relief) - Not for 230VAC use	\$18.00
SMP50	Surface Mounting Plate	\$20.00
RA™	Remote Alarm	\$165.00
VR™	Power Supply, 24VAC, 20VA. (indoor use only)	\$34.00
CS-11	20 Megohm Resistivity Calibration Module (sensor substitute) NIST Traceable	\$37.00
CS-14	2 Megohm Resistivity Calibration Module (sensor substitute) NIST Traceable	\$37.00
CS-17	200 Kiloohm Resistivity Calibration Module (sensor substitute) NIST Traceable	\$37.00
RC	NIST Certificate (without sensor)	\$35.00
CSC	Cell Sub Certificate	\$25.00

* Does not fit into enclosure, must be mounted separately.

For sensor selection see Sensor Selection Guide.

**MYRON L
COMPANY**

pH/Conductivity Instrumentation
Accuracy • Reliability • Simplicity

750 SERIES II RANGE SELECTION GUIDE

RESISTIVITY

Resistivity requires CS10 Sensor or equivalent (0.05 constant)

Add Range NUMBER below to instrument model number, i.e. 753II-"11" = 0-20 megohms Digital Monitor/controller.

RANGE

751II, 752II, 753II & 754II

Resistivity

0-20 MΩ	-11
0-10 MΩ	-12
0-5 MΩ	-13
0-2 MΩ	-14
0-1 MΩ	-15
0-500 KΩ	-16
0-200 KΩ	-17

ALL SPECIAL ORDER ITEMS ARE NON-RETURNABLE AND NON-REFUNDABLE.

Custom and OEM Monitors/controllers available, contact us with your special needs. Price and delivery upon request.

Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.

Because of our policy of continuous product improvement, the Myron L Company reserves the right to make changes in design, specifications, and prices without notice.

Terms: 1% 10 days, net 30 days upon receipt of sufficient credit information.

Export orders: payment in advance, sight draft collection, or credit card.

6115 Corte del Cedro
Carlsbad, CA 92009-1516 USA
Tel: 760-438-2021
Fax: 800-869-7668 / 760-931-9189
www.myronl.com

Built On Trust. Founded in 1957, the Myron L Company has become one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

