










Resistivity & Conductivity/TDS Sensor Selection Guide

		- WITH TEE FITTING (BY CUSTOMER)								
		INSERTION	SUBMERSION	FLOW THROUGH	LOW RANGE (K-0.05 & 0.1)	MEDIUM RANGE (K-1.0)	HIGH RANGE (K-10.0)	MAXIMUM PRESSURE AND TEMPERATURE.	KEY FEATURES	
CS10 316SS TEFLON		3/4" NPT STD ● 1/2" NPT OPT ●	●	●	●			100 PSI AT 100°C	High Purity Water	
CS40 316SS TEFLON		1" NPT VALVE ● 3/4" NPT ●	●		●	●	●	100 PSI AT 150°C 250 PSI AT 205°C (HT OPTION)	Valve Insertable Wide Range of Measurement	
CS41 316SS TEFLON		3/4" NPT ●	●	●	●	●		100 PSI AT 150°C 250 PSI AT 205°C (HT OPTION) 400 PSI AT 100°C	Boiler & Condensate Service	
CS50 316SS CPVC		1" NPT ●	●	●	●	●		100 PSI AT 95°C	Low Cost	
CS51 CS51LC 316SS TEFLON		3/4" NPT STD ● 1/2" NPT OPT ●	●	●	●	●		100 PSI AT 100°C	Low Cost Small Size	
CS52 316SS CPVC		3/4" NPT ●		●			●	100 PSI AT 95°C	High Range Low Cost	
CS52B 316SS POLYPRO CPVC		3/4" NPT ●	●	●			●	100 PSI AT 95°C	May be hung by its cable in a tank.	
CS60 316SS KYNAR TEFLON		1" NPT ●	●	●	●	●		100 PSI AT 120°C	Excellent Chemical Resistance	
CSA CSATC 316SS ABS PLASTIC		3/4" NPT ●		●		●		75 PSI AT 60°C	Extremely Low Cost	

MYRON L COMPANY
pH/Conductivity Instrumentation
Accuracy • Reliability • Simplicity

6115 Corte del Cedro
Carlsbad, CA 92009-1516 USA
Tel: 760-438-2021
Fax: 800-869-7668 / 760-931-9189